

D¹
a flexible catheter which is adapted to be introduced into the body lumen through a first access penetration in the lumen wall and advanced along the length of the body lumen; and

means advancable from the catheter for creating a second access penetration in the lumen wall and providing a filament path along the length of the body lumen between said first and second access penetrations, the means advancable also being retractable into the catheter after creating the second access penetration.

D² Sub E¹
42. (Amended) A device for positioning a filament in a body lumen, said device comprising:

a flexible catheter which can be introduced through a first access penetration into the body lumen and advanced along the length of the body lumen, said catheter having a proximal end, a distal end, and a lumen therethrough;

a guide tube reciprocatably disposed in the lumen of the catheter so that the guide tube can be advanced from the distal end of the catheter, said guide tube having a proximal end, a distal end, and a lumen therethrough, wherein the distal end of the guide tube is deflectable; and

a penetrating element reciprocatably mounted in the lumen of the guide tube so that the penetrating element can be advanced from the distal end of the guide tube to penetrate a luminal wall in a direction determined by deflection of the distal end of the guide tube creating a second access penetration and providing a filament path along the length of the body lumen between the first and second access penetrations, and so that the penetrating element can be retracted after creating the second access penetration.

APPENDIX B
CLEAN VERSION OF ALL PENDING CLAIMS

Claims 1-32 have been previously cancelled.

33. (Twice Amended) A device for positioning a filament in a body lumen having lumen walls, said device comprising:

a flexible catheter which is adapted to be introduced into the body lumen through a first access penetration in the lumen wall and advanced along the length of the body lumen; and

means advancable from the catheter for creating a second access penetration in the lumen wall and providing a filament path along the length of the body lumen between said first and second access penetrations, the means advancable also being retractable into the catheter after creating the second access penetration.

34. (As filed) A device as in claim 33, wherein the catheter has at least one lumen therethrough and the advancable means is reciprocatably received in the catheter lumen.

35. (As filed) A device as in claim 34, wherein the advancable means has a pre-formed tip which deflects laterally as it is advanced from the catheter.

36. (Previously Amended) A device as in any of claims 33 to 35, wherein the advancable means comprises a guide tube having a lumen therethrough and a penetrating element removably received in the lumen and extending from a distal tip of the guide tube, wherein the penetrating element can be withdrawn from the guide tube after the guide tube has been placed between the access penetrations to leave the guide tube lumen as the filament path.

37. (As filed) A device as in claim 36, wherein the penetrating element is a stylet.

38. (As filed) A device as in any of claims 33 to 35, further comprising an expandable anchor disposed over at least a portion of the catheter.

Claims 39 through 41 have been previously cancelled.

42. (Amended) A device for positioning a filament in a body lumen, said device comprising:

a flexible catheter which can be introduced through a first access penetration into the body lumen and advanced along the length of the body lumen, said catheter having a proximal end, a distal end, and a lumen therethrough;

a guide tube reciprocatably disposed in the lumen of the catheter so that the guide tube can be advanced from the distal end of the catheter, said guide tube having a proximal end, a distal end, and a lumen therethrough, wherein the distal end of the guide tube is deflectable; and

a penetrating element reciprocatably mounted in the lumen of the guide tube so that the penetrating element can be advanced from the distal end of the guide tube to penetrate a luminal wall in a direction determined by deflection of the distal end of the guide tube creating a second access penetration and providing a filament path along the length of the body lumen between the first and second access penetrations, and so that the penetrating element can be retracted after creating the second access penetration.

43. (As filed) A device as in claim 42, wherein the guide tube has a pre-formed tip which deflects laterally as the guide tube is advanced from the catheter.

44. (As filed) A device as in claim 42, wherein the penetrating element is a stylet.

45. (As filed) A device as in any of claims 42 to 44, further comprising an expandable anchor disposed over at least a portion of the catheter.